

# ARTCOOL MIRROR



LG participates in the ECP programme for EUROVENT AC program. Check ongoing validity of certification: [www.eurovent-certification.com](http://www.eurovent-certification.com)

Embedded Wi-Fi	Smart Diagnosis	Active Energy Control	Energy Display	Plasmaster Ionizer <sup>PLUS</sup>	Plasmaster Auto Cleaning		
Jet Cool	4 Way Swing	Fast Heating	Gold Fin™	Comfort Air	Low Noise 19dB (9k, 12k)	Silent Mode	Quick & Easy Installation

## • Single Combination

UNIT				9K	12K	18K	24K
INDOOR				AC09BQ NSJ	AC12BQ NSJ	AC18BQ NSK	AC24BQ NSK
Capacity	Cooling	Min / Rated / Max	W	890 / 2,500 / 3,700	890 / 3,500 / 4,040	900 / 5,000 / 5,500	900 / 6,600 / 7,420
	Heating	Min / Rated / Max	W	890 / 3,300 / 4,100	890 / 4,000 / 5,100	900 / 5,800 / 6,400	900 / 7,500 / 8,640
	Heating -7°C	Rated	W	2,600	3,000	4,200	6,000
Power Input	Cooling	Rated	W	656	1,080	1,562	2,164
	Heating	Rated	W	800	1,050	1,611	2,238
EER			W / W	3.81	3.24	3.20	3.05
S.E.E.R.				7.0	6.6	7.0	6.9
P design C			kW	2.5	3.5	5.0	6.6
COP			W / W	4.13	3.81	3.60	3.35
S <sub>c</sub> C <sub>o</sub> P <sub>r</sub> (Average / Warmer)				4.0 / 4.9	4.0 / 4.9	4.3 / 5.3	4.3 / 5.3
P design H (Average / Warmer)			kW	2.5 / 1.3	2.5 / 1.3	3.9 / 2.1	5.0 / 2.7
Energy Label (A+++ to D Scale)	Cooling			A++	A++	A++	A++
	Heating (Average / Warmer)			A+ / A++	A+ / A++	A+ / A+++	A+ / A+++
Annual Energy Consumption	Cooling		kWh	125	186	250	335
	Heating (Average / Warmer)		kWh	875 / 371	875 / 371	1270 / 555	1628 / 713
Sound Pressure	Cooling	S / L / M / H	dB(A)	19 / 27 / 35 / 41	19 / 27 / 35 / 41	31 / 34 / 39 / 44	31 / 34 / 42 / 47
	Heating	L / M / H	dB(A)	27 / 35 / 41	27 / 35 / 41	34 / 39 / 44	34 / 42 / 47
Sound Power	Cooling	Power	dB(A)	59	59	60	65
	Heating	S / L / M / H	m <sup>3</sup> / min	3.0 / 4.2 / 7.5 / 10.0	3.0 / 4.2 / 7.5 / 10.0	8.0 / 10.5 / 13.0 / 14.5	8.0 / 10.5 / 13.1 / 16.1
Air Flow Rate	Cooling	Max (Power)	m <sup>3</sup> / min	12.5	12.5	15.5	20.0
	Heating	L / M / H	m <sup>3</sup> / min	5.6 / 7.2 / 10.0	5.6 / 7.2 / 10.0	11.0 / 13.5 / 16.0	10.5 / 13.1 / 16.1
Dehumidification Rate			l/h	1.1	1.3	1.8	2.5
	Cooling	Rated	A	3.3	4.7	6.9	9.8
Running Current		Max	A	6.0	6.0	9.0	14.0
	Heating	Rated	A	4.0	4.7	7.1	10.4
		Max	A	7.0	7.0	9.5	14.0
Starting Current	Cooling / Heating	Rated	A	3.3 / 4.0	4.7 / 4.7	6.9 / 7.1	9.8 / 10.4
Power Supply			∅, V, Hz	1, 220-240, 50	1, 220-240, 50	1, 220-240, 50	1, 220-240, 50
Circuit Breaker			A	15	15	20	25
Power Supply Cable			N x mm <sup>2</sup>	3 x 1.0	3 x 1.0	3 x 1.5	3 x 2.5
Power & Transmission Cable			N x mm <sup>2</sup>	4 x 1.0	4 x 1.0	4 x 1.0	4 x 1.0
				(Including Earth)	(Including Earth)	(Including Earth)	(Including Earth)
Dimension			mm	837 x 308 x 192	837 x 308 x 192	998 x 345 x 212	998 x 345 x 212
Net Weight			kg	9.9	9.9	12.8	13.5
Fan Motor Output			W	30	30	30	60
OUTDOOR				AC09BQ UA3	AC12BQ UA3	AC18BQ UL2	AC24BQ U24
Operation Range	Cooling	Min / Max	°CDB	-10 / 48	-10 / 48	-15 / 48	-15 / 48
	Heating	Min / Max	°CDB	-10 / 24	-10 / 24	-10 / 24	-10 / 24
Sound Pressure	Cooling	High	dB(A)	48	48	53	54
	Heating	High	dB(A)	50	50	55	57
Sound Power	Cooling	High	dB(A)	65	65	65	70
	Heating	High	dB(A)	65	65	65	70
Air Flow Rate	Cooling	High	m <sup>3</sup> / min	27	27	35	50
	Heating	High	m <sup>3</sup> / min	27	27	35	50
Piping	Length (Odu / Idu)	Min / Max	m	3 / 15	3 / 15	3 / 20	3 / 30
	Elevation (Odu / Idu)	Max	m	7	7	10	15
Piping Connection	Liquid	OD (Outside)	mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	OD (Outside)	mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)	15.88 (5/8)
Drain Hose Size		OD (Outside)	mm (inch)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)	21.5 (0.85)
	Type			R32	R32	R32	R32
Refrigerant	Charge at 7.5m		kg	0.700	0.700	1.000	1.100
			t-CO <sub>2</sub> eq	0.473	0.473	0.675	0.743
	Additional charge		g/m	20	20	20	20
	GWP			675	675	675	675
Fan Motor Output			W	43	43	43	85
Compressor Type				Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary
Net Weight			kg	26.0	26.0	35.2	46.4
Dimension			mm	717 x 495 x 230	717 x 495 x 230	770 x 545 x 288	870 x 650 x 330

※ This product contains Fluorinated greenhouse gases (R32).  
 ※ S : Sleep / L : Low / M : Medium / H : High  
 ※ GWP : Global warming potential  
 ※ t-CO<sub>2</sub>eq : F-gas(kg)\*GWP/1000  
 ※ Specification, design and feature are subject to change without prior notice.