




OUTDOOR UNITS



FM41AH
FM49AH
FM57AH

(Unit : mm)



OUTDOOR				FM41AH U34	FM49AH U34	FM57AH U34
Compressor	Type			Scroll	Scroll	Scroll
Capacity*	Cooling	Min / Nom / Max	kW	2.8 / 12.3 / 15.4	3.3 / 14.1 / 17.0	4.0 / 15.5 / 18.5
	Heating	Min / Nom / Max	kW	3.1 / 13.5 / 16.2	3.7 / 16.0 / 17.3	4.5 / 17.4 / 18.8
Low Temperature Capacity	Heating	Max	kW	12.5	14.5	15.5
Power Input*	Cooling	Min / Nom / Max	kW	0.82 / 2.42 / 4.90	0.96 / 3.12 / 5.30	1.18 / 3.87 / 5.60
	Heating	Min / Nom / Max	kW	0.89 / 2.87 / 5.10	1.06 / 3.76 / 5.40	1.29 / 4.34 / 5.80
Running Current*	Cooling	Min / Nom / Max	A	1.2 / 3.6 / 7.4	1.4 / 4.7 / 8.0	1.8 / 5.8 / 8.4
	Heating	Min / Nom / Max	A	1.3 / 4.3 / 7.7	1.6 / 5.7 / 8.1	1.9 / 6.5 / 8.7
EER				5.08	4.51	4.01
COP				4.70	4.25	4.01
SEER				7.40	7.20	6.90
SCOP				4.20	4.20	4.20
Pdesign(@-10°C)			kW	8.6	9.5	9.5
Seasonal Energy Label (A++ to E Scale)	Cooling / Heating			- / -	- / -	- / -
Annual Energy Consumption	Cooling / Heating	kWh		981 / 2,867	1,167 / 3,167	1,348 / 3,167
Air Flow Rate	Nom	m ³ /min x No.		110	110	110
Sound Pressure Level	Cooling	Nom	dB(A)	51	53	53
	Heating	Nom	dB(A)	53	55	55
Sound Power Level	Cooling	Max	dB(A)	69	71	73
	Heating	Max	dB(A)	70	72	74
Dimensions	W x H x D	mm		950 × 1,380 × 330	950 × 1,380 × 330	950 × 1,380 × 330
Net Weight			kg	87	87	87
Refrigerant	Type			R410A	R410A	R410A
	Charge	kg		4,200	4,200	4,200
	Additional Charging Volume	g/m		20	20	20
	GWP (Global Warming Potential)			2,087.5	2,087.5	2,087.5
	t-CO ₂ eq			8,768	8,768	8,768
Operation Range (Outdoor)	Cooling	Min - Max	°C DB	-10 - 48	-10 - 48	-10 - 48
	Heating	Min - Max	°C WB	-25 - 18	-25 - 18	-25 - 18
Power Supply			Ø, V, Hz	3, 380-415, 50	3, 380-415, 50	3, 380-415, 50
Power Supply Cable			No. x mm ²	5C × 2.5	5C × 2.5	5C × 2.5
Transmission Cable	ODU-BD	No. x mm ²		4C × 1.25	4C × 1.25	4C × 1.25
	BD-IDU	No. x mm ²		4C × 0.75	4C × 0.75	4C × 0.75
Circuit Breaker			A	20	20	20
Max Piping Length	Total Piping(Main+Total Branch)		m	125	135	145
	Main Piping		m	55	55	55
	Total Branch Piping		m	70	80	90
	Each Branch Piping		m	15	15	15
Piping Elevation Difference	IDU-ODU	Max	m	30	30	30
	IDU-IDU	Max	m	15	15	15
Piping Connections	Liquid	mm (inch) x No.		Ø9.52 × 1	Ø9.52 × 1	Ø9.52 × 1
	Gas	mm (inch) x No.		Ø19.05 × 1	Ø19.05 × 1	Ø19.05 × 1

※ For our policy of continuous product improvement, specification, design and features are subject to change without prior notice.

※ This Product is available from Apr.2020

Note : 1. Capacities are based on the following conditions:

Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB

Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB

Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.

2. * : See page "Combination Table".

3. Due to our policy of innovation some specifications may be changed without notification.

4. At least two indoor units should be connected.

5. Minimum combination capacity rate should be more than 40%.

6. This product contains fluorinated greenhouse gases. (R410A)