## **Product Information**



## PRODUCT FICHE

Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

Heat pump space heater		No label found for faw.heatpump.singl	EDLA09DA3W1
pace Heating	Energy efficiency class 55°C (High temp. app.) Energy efficiency class 35°C (Low temp. app.)	-	A++ A+++
Average climate (Design temperature = -10°C) Space heating 55°C			
	Prated (declared heating capacity) @ -10°C	[kW]	9.0
	Seasonal space heating efficiency (η <sub>S</sub> )	[%]	133
	Annual energy consumption	[kWh]	5,488
Space heating 35°C	Prated (declared heating capacity) @ -10°C	[kW]	9.0
	Seasonal space heating efficiency (η <sub>S</sub> )	[%]	186
	Annual energy consumption	[kWh]	3,939
ff peak operation function integrated in Heat pump	Annual energy consumption	Y/N	false
older climate (Design temperature = -22°C) pace heating 55°C		[kW]	9.0
	Prated (declared heating capacity) @ -22°C		
	Seasonal space heating efficiency $(\eta_S)$	[%]	121
	Annual energy consumption	[kWh]	7,142
Space heating 35°C	Prated (declared heating capacity) @ -22°C	[kW]	9.0
	Seasonal space heating efficiency (η <sub>S</sub> )	[%]	173
	Annual energy consumption	[kWh]	5,031
Warmer climate (Design temperature = 2°C) Space heating 55°C		FLAAD	
	Prated (declared heating capacity) @ 2°C	[kW]	9.0
	Seasonal space heating efficiency (η <sub>S</sub> )	[%]	162
	Annual energy consumption	[kWh]	2,921
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	9.0
	Seasonal space heating efficiency $(\eta_S)$	[%]	233
	· ·	[kWh]	2,039
ound Power (*)	Annual energy consumption	[dB(A)]	62.0
codesign technical data			
Product description	Air-to-water heat pump: Water-to-water heat pump:	<u>Y/N</u> <u>Y/N</u>	Yes No
	Brine-to-water heat pump:	Y/N	No
	Low-temperature heat pump: Equipped with a supplementary heater:	Y/N Y/N	No Yes
	For heat pump combination heater:	Y/N	No
ir to water unit	Rated airflow (outdoor)	[m <sup>3</sup> /h]	2,880
rine/water to water unit	Rated water/brine flow (outdoor H/E)	[m <sup>3</sup> /h]	
Other	Capacity control	<u>-</u> [kW]	Inverter 0.023
	Poff (Power consumption Off mode)	[KVV]	
	Pto (Power consumption Thermostat off mode)	[kW]	0.023
	P <sub>Sb</sub> (Power consumption Standby mode)	[kW]	0.023
	<del></del>	[kW]	0.000
	PCK (Power crankcase heater model)		0.000
	Q <sub>elec</sub> (Daily electricity consumption)	[kWh]	
	Qf <sub>UC</sub> ( Daily fuel consumption )	[kWh]	
art load conditions space heating average climate	1001		
(A) condition (-7°C)	P <sub>dh</sub> (declared heating capacity)	[kW]	8.5
			2.09
	COP <sub>d</sub> (declared COP)		
3) condition (2°C)	Cdh (degradation coefficient)		5.0
	Pdh (declared heating capacity)		
	COP <sub>d</sub> (declared COP)		3.28
	Cdh (degradation coefficient)		1.0
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.4
	COP <sub>d</sub> (declared COP)	-	4.80
	Cdh (degradation coefficient)	-	1.0
(D) condition (12°C)	P <sub>dh</sub> (declared heating capacity)	[kW]	5.3
		-	6.45
	COP <sub>d</sub> (declared COP)		
(E) Tol (temperature operating limit)	Cdh (degradation coefficient)  Tol (temperature operating limit)	- [°C]	1.0 -10
	Pdh (declared heating capacity)	[kW]	6.8
	<del></del>	-	1.70
	COPd (declared COP)	F-07	
(F) No label found for faw.tbivalent.temperaturee.	WTOL (Heating water Operation Limit)	[°C] [°C]	-8
	™blv		
	Pdh (declared heating capacity)	[kW]	8.8
	COPd (declared COP)	-	1.92
apacity of the back-up heater integrated in the unit		[kW]	
	P <sub>SUD</sub> back-up heater (@Tdesignh: -10°C)	•	
Supplementary capacity at P_design		[kW]	2.2

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu.'

Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3 This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer. Depending on your application and the product selected an additional supplementary heater may have to be installed.