

PRODUCT FICHE

Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

Heat pump space heat	ter	Outdoor Indoor	EPRA16DAW1 ETBH16DA9W
pace Heating	Energy efficiency class 55°C (High temp. app.)		A++
waraga alimata (Dagiga tamparatura = 40°C)	Energy efficiency class 35°C (Low temp. app.)	-	A+++
Average climate (Design temperature = -10°C) Space heating 55°C Space heating 35°C	Prated (declared heating capacity) @ -10°C	[kW]	13
		[%]	140
	Seasonal space heating efficiency (η _S)		
	Annual energy consumption	[kWh] [kW]	7,236 13
	Prated (declared heating capacity) @ -10°C		
	Seasonal space heating efficiency $(\eta_{\hat{S}})$	[%]	186
	Annual energy consumption	[kWh]	5,479
ff peak operation function integrated in Heat pump older climate (Design temperature = -22°C)		Y/N	false
Space heating 55°C	Prated (declared heating capacity) @ -22°C	[kW]	13
		[%]	125
	Seasonal space heating efficiency (n _S)		
Space heating 35°C	Annual energy consumption	[kWh] [kW]	9,658 13
	Prated (declared heating capacity) @ -22°C		
	Seasonal space heating efficiency (η_S)	[%]	163
	Annual energy consumption	[kWh]	7,425
Warmer climate (Design temperature = 2°C) Space heating 55°C	D (declared heating sourceits) @ 2°C	[kW]	13
	Prated (declared heating capacity) @ 2°C		
	Seasonal space heating efficiency $(\eta_{\mbox{\scriptsize S}})$	[%]	161
Curan hasting 2500	Annual energy consumption	[kWh]	4,063
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	13
	Seasonal space heating efficiency (η _S)	[%]	220
	Annual energy consumption	[kWh]	2,992
ndoor sound power (*)	Annual energy consumption	[dB(A)]	44.0
utdoor sound power (*)		[dB(A)]	54.0
codesign technical data	Air-to-water heat pump:	Y/N	Yes
Product description	Water-to-water heat pump:	Y/N	No
	Brine-to-water heat pump:	Y/N Y/N	No No
	Low-temperature heat pump: Equipped with a supplementary heater:	<u>Y/N</u>	Yes
in 40	For heat pump combination heater:	Y/N 3	Yes
ir to water unit rine/water to water unit	Rated airflow (outdoor)	[m ³ /h]	
	Rated water/brine flow (outdoor H/E)	[m ³ /h]	
Other	Capacity control	<u>-</u> [kW]	Inverter 0.031
	Poff (Power consumption Off mode)		
	Pto (Power consumption Thermostat off mode)	[kW]	0.033
	P _{Sb} (Power consumption Standby mode)	[kW]	0.042
		[kW]	0.000
	PCK (Power crankcase heater model)		
	Qelec (Daily electricity consumption)	[kWh]	
	Qfuel(Daily fuel consumption)	[kWh]	
art load conditions space heating average climate			
A) condition (-7°C) B) condition (2°C)	Poh (declared heating capacity)	[kW]	11.1
	3		2.43
	COP _d (declared COP)		
	Cdh (degradation coefficient)	- [kW]	1.0 6.7
	Pdh (declared heating capacity)	[KVV]	
	COP _d (declared COP)	-	3.52
			1.0
	Cdh (degradation coefficient)		1.0
c) condition (7°C)	•	[kW]	6.5
c) condition (7°C)	Cdh (degradation coefficient) Pdh (declared heating capacity)	- [kW]	
c) condition (7°C)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP)	[kW]	6.5 4.54
	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient)	- [kW] - - - [kW]	6.5
	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP)	-	6.5 4.54 1.0 5.2
	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient)	-	6.5 4.54 1.0
)) condition (12°C)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient)	- [kW]	6.5 4.54 1.0 5.2 5.97
)) condition (12°C)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit)	- [kW] - - - [°C]	6.5 4.54 1.0 5.2 5.97
)) condition (12°C)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient)	- [kW]	6.5 4.54 1.0 5.2 5.97 1.0 -10 12.5
D) condition (12°C)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit)	- [kW] - - - [°C]	6.5 4.54 1.0 5.2 5.97
D) condition (12°C)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) Pdh (declared heating capacity)	- [kW] - - - [°C]	6.5 4.54 1.0 5.2 5.97 1.0 -10 12.5 2.12
D) condition (12°C) E) Tol (temperature operating limit)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (degradation coefficient) Tol (temperature operating limit) Pdh (declared heating capacity) COPd (declared COP)	[kW]	6.5 4.54 1.0 5.2 5.97 1.0 -10 12.5 2.12
C) condition (7°C) D) condition (12°C) E) Tol (temperature operating limit) F) No label found for faw.tbivalent.temperaturee.	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) Pdh (declared heating capacity) COPd (declared COP) WTOL (Heating water Operation Limit)	- [kW] - - [°C] [kW] -	6.5 4.54 1.0 5.2 5.97 1.0 -10 12.5 2.12
D) condition (12°C) E) Tol (temperature operating limit)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) Pdh (declared heating capacity) COPd (declared COP) WTOL (Heating water Operation Limit)	- [kW] - - [°C] [kW] - [°C]	6.5 4.54 1.0 5.2 5.97 1.0 -10 12.5 2.12 55 -10 12.5
D) condition (12°C) E) Tol (temperature operating limit)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) Pdh (declared heating capacity) COPd (declared COP) WTOL (Heating water Operation Limit)	- [kW] - - [°C] [kW] - [°C]	6.5 4.54 1.0 5.2 5.97 1.0 -10 12.5 2.12 55 -10
D) condition (12°C) Tol (temperature operating limit)	Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Pdh (declared heating capacity) COPd (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) Pdh (declared heating capacity) COPd (declared COP) WTOL (Heating water Operation Limit) TblV Pdh (declared heating capacity)	- [kW] - - [°C] [kW] - [°C]	6.5 4.54 1.0 5.2 5.97 1.0 -10 12.5 2.12 55 -10 12.5

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu.'

Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3

This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.

Depending on your application and the product selected an additional supplementary heater may have to be installed.